

FloorLabs

One Step Ahead



- THIS IS THE EXCELLENT PRODUCT FOR PARQUET FLOORING
- NO NEED ANY GLUE OR BAND
- DURABLE FOR MOISTURE AND WATER
- EXCELLENT HEAT INSULATION
- SOUND INSULATION TO 23DB
- BRING INTO EXISTENCE STRAIGHT AND DURABLE SURFACE AFTER OBVIATE THE ROUGHNESS AND CRACKS OF THE FLOORING
- PROVIDE AN OPPORTUNITY TO PUT IN CABLES UNDER THE PARQUET BECAUSE OF ITS KIND OF THICKNESS AND STRUCTURE
- CAN NOT USE FOR HEAT INSULATION

Fiziksel Özellikler / Physical features	KP3	KP5
Kalık / Thickness	3 mm	5 mm
Ebat / Proportion	80 cm x 125 cm	
Yoğunluk / Intensity	40 Kg / m ³	35 Kg / m ³
Yüzey Kaplaması / Surface coating	Yok / No	
Yüzey Tipi / Surface type	Pürüzsüz / Smooth	
Isı İletkenliği / Heat conductivity	0.035 W / mk	
Isı Geçirgenlik Direnci / Heat transmissivity resistance	0,086 mm ² K / W	0,15 m ² K / W
Su Buharı Direnci / Water vapor resistance	750	650
Su Emme Özelliği / Water absorption property	Yok	
Ses İzolasyonu / Voice isolation	16 - 17 dB	
Basma Mukavemeti / Compression strength	0,1 N / mm ²	
Çekme Mukavemeti / Tensile strength	1,3 N / mm ²	1,1 N / mm ²
Dayanım Sıcaklığı / Resistance temperature	-60 oc +70 °C	